



DPS2050Hw

Single-direction vibratory plates

Powerful and versatile on all surfaces

The DPS single-direction vibratory plate provides powerful compaction results on soil and asphalt and is ideally suited for use on on top and base layers. It was designed for tough, long-term application on the construction site. The diesel engine, equipped with large power reserves, the wear-resistant base plate from ductile graphite iron (GJS 700), we well as the maintenance-free and durable exciter bearing all contribute to the plate's long life and durability. The easy to reach throttle lever and vibration damped guide handle offer a high degree of operating comfort.

Highlights

- Excellent turning ability and control with simultaneously low HAV
- Wide, ergonomic handle
- Control handle
- Wheel set quickly ready for use
- Paving pad device easy to mount
- Large water tank {{8 Liter}}(2.11 gal) with efficient sprinkler system
- Permanently lubricated ball bearings

Technical Data

■ Mechanical - Output Details

Centrifugal force	20 kN
Area capacity	660.0 m NN
Forward Running	22.0 m/min
Gradeability	36.4 %
Vibrations (Hz)	98.0 Hz

■ Mechanical Details

Length Baseplate	599.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	663.0 mm

Height Cover frame	663.0 mm
Thickness Baseplate	9.0 mm
Operating weight	114.9 kg
Ground clearance	663.0 mm

■ Engine

Effective power	3.4 KW
Nominal Engine speed	3,400.0 kg/m2s

■ Environment Data

HAV summation (average value)	3.1 m/s2
HAV summation (Standard)	EN 500-4

Available engines

Hatz 1B20-7-333A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	243 cm ³
Fuel	Diesel EN 590
Fuel consumption	0.40 L/hr
Tank capacity	3.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz